

PACIFICA

SURFACES:

All Pacifica panels are made from abundant jobsite wood and reconstructed resulting in a durable and unique looking panel. No two panels are identical due to the slight variations in color and pattern from the recycled wood. The Pacifica panels are filled with a sustainable wood filler to help eliminate the natural occurring voids.

HANDLING:

Store Pacifica panels in a climate controlled area on a flat, level surface with adequate support.

FABRICATION:

Pacifica panels require the same fabrication equipment, techniques, and products as typical wood substrates. No unique technology is required.

MACHINING AND FASTENING:

Pacifica panels are worked using standard fabricating techniques applicable for plywood panel products and will accept standard fasteners and woods adhesives. Care should be taken when cutting and machining Pacifica, as the edges can splinter. TorZo recommends a minimum of 3/16" round over on all exposed edges for best results.

FINISHING:

Pacifica panels are shipped from the warehouse unfinished, unless otherwise indicated. As part of the fabrication process, each panel requires a clear sealer and finishing topcoat, which is typically polyurethane, lacquer, or other approved products.

SUSTAINABILITY:

- FSC– Certified wood (at least 50%)
- No added urea formaldehyde
- Certified low VOC Performance
- Waste to Energy

KEY FEATURES

- Made from Recycled wood linear aesthetic
- Proven Durability

IDEAL FOR:

- Wall Paneling
- Table & Countertops
- Furniture
- Flooring

TORZOSURFACES.COM



THICKNESS	1/4" to 1-1/2"
WIDTH	47", 48"
LENGTH	95", 96"
DENSITY	46LBS
INTERNAL BOND	222.3 PSI
MOR	2,108 PSI
HARDNESS	592.3 LBS
SCREW HOLDING FACE	104.9 LBS Req to pull 1" #10 Sheet Metal Screw
SCREW HOLDING EDGE	122.4 LBS Req to pull 1" #10 Sheet Metal Screw
FIRE RATING	Can be A or B with Proper Coating